

Multi-Purpose Harness - Linq

Linq's Multi-Purpose Harness is suitable for Fall Arrest, Construction, Ladder, Scaffolding, Warehouse, Confined Space and Positioning Restraint environments.

Key Features:

- Weight: 2.6kg
- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment
- Liqui-Pel Technology for liquid protection, also easier to clean the harness
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation
- Retro-Reflective Thread in webbing for improved visibility in low light
- Rear Barr D allows easier access and better weight distribution for twin retractable fall arrest devices
- Closed Loop Webbing system on rear Dorsal Barr D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning as per AS/NZS requirements
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from



| SKU/Part # | Size |
|---------------------|--------------|
| HARNESS-H302-S | SMALL |
| HARNESS-H302-M/L | STANDARD M L |
| HARNESS-H302-XL/2XL | MAXI XL 2XL |



**Guaranteed.
Tested.
In Stock.**

Product Data Sheet

hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker

- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap
- Comes with Suspension Trauma Strap: One-piece Webbing with a quick connection buckle for faster deployment and connection in the event of a fall
- Air COOL Padded Shoulder Straps for increased comfort and increased air flow during long periods of use
- Padded Legs for force dispersion at moment of fall impact
- Confined Space Rescue Loops
- Adjustable Waist Belt with tool loop attachments
- Service Pouch on back
- 10 year life span from date of manufacture

Standards:

- AS/NZS 1891.1

