





Guaranteed. Tested. In Stock.

Product Data Sheet

om Self Retracting Lifeline -Linq

Ling's 6m Self Retracting Lifeline is engineered for extreme workplace situations, boasting compliance with AS/NZS 1891.3 section 1.6. LINQ's 6m self retracting lifeline extend and retract automatically. allowing the user to operate within the recommended work area permitted by the AS/NZS Standard. The lifeline maintains tension which clears the work zone of any loose and dangerous excess webbing. In the event of a fall, a brake activates, arresting the fall and reduces the impact of the fall.

Key Features:

- Weight: 1.65kg + / 10gm
- Retractable webbing maximum length: 6m
- Minimum Breaking Strength > 15 kN
- Anchorage eye with swivel action prevents undue twisting of rope while working or in the event of a fall
- Comes with load indicator snap hook
- High impact polymer outer casing

Standards:

- AS/NZS 1891.3 section 1.6
- EN 360
- ISO 9227



SKU/Part # LANYARD-L-IRRWL600

