

Product Data Sheet

Modiewark Phasing Spout Kit 2 1200mm - G.L McGavin

G.L McGavin's Modiewark Phasing Spout Kit 2 with 1200mm hot stick is designed specifically for testing live or dead spout applications from 240V up to 33kV. The Modiewark AC Non-Contact Spout tester can be used on inside applications up to 33kV on metal clad switch gear. This Modiewark Phasing Spout Kit is designed to be used above 600 volts and is supplied with an Electrical certificate (Certificate is for Stick and Spout).

If both testers activate at the same time and the light is green, the two sources are the same phase.

If both testers activate at the same time and the green light is out the two sources are not the same phase.

Key Features:

- Frequently purchased Non-Contact Spout Tester Models:
 - MWB - OFF, 240V, 3.3kV, 6.6kV, 11kV, 22kV, 33kV
 - S4B - OFF, 240V, 2kV, 6.6kV, 11kV
 - RTC - OFF, 240V, 5kV, 6.6kV, 11kV, 12.7kV, 22kV, 33kV
 - Other models and options are located within the [More Information](#) tab.
 - If you require a Custom product, or other models not listed on the website please enter the relevant information



SKU/Part #	Spout-length / Model
MET-M-PHASE-KIT-2-150-RTC	150mm / Rtc
MET-M-PHASE-KIT-2-150-S4B	150mm / S4b
MET-M-PHASE-KIT-2-150-OTHER	150mm / Other
MET-M-PHASE-KIT-2-150-MWB	150mm / Mwb
MET-M-PHASE-KIT-2-150-CUSTOM	150mm / Custom
MET-M-PHASE-KIT-2-200-RTC	200mm / Rtc
MET-M-PHASE-KIT-2-200-S4B	200mm / S4b
MET-M-PHASE-KIT-2-200-OTHER	200mm / Other
MET-M-PHASE-KIT-2-200-MWB	200mm / Mwb
MET-M-PHASE-KIT-2-200-CUSTOM	200mm / Custom
MET-M-PHASE-KIT-2-300-RTC	300mm / Rtc
MET-M-PHASE-KIT-2-300-S4B	300mm / S4b



**Guaranteed.
Tested.
In Stock.**

Product Data Sheet

in the cart checkout page under 'Order Notes'.

- Proximity Tester:
 - Size: 23cm x 10cm x 10cm
 - Colour: Orange
 - Weight: 900g
 - Operating Temperature: -10C - 65C
 - Made in Australia
 - Suitable to combine with most insulated sticks
 - Multiple models to detect different voltage ranges
 - Comes with 3 x C batteries to ensure on-site readiness
 - Self test function to verify tester is working appropriately
 - Easy selection wheel to change voltage source detection value
 - Loud 85dB buzzer sound to allow for audible detection of voltage source
 - Bright red detection light allows for visual detection of voltage source in noisy environments
 - Identification of the voltage source detection values from 200mm - 300mm away from the voltage source

MET-M-PHASE-KIT-2-300-OTHER

300mm /
Other

MET-M-PHASE-KIT-2-300-MWB

300mm /
Mwb

MET-M-PHASE-KIT-2-300-CUSTOM

300mm /
Custom

Standards:

- IP63





**Guaranteed.
Tested.
In Stock.**

Product Data Sheet

Kit Contents:

- 2 x Modiewark AC Tester to 33kv (Includes Spout Attachment)
- 1 x Hard Plastic Protection Case with Foam Insert to suit spout length
- 2 x 1200 mm hot stick with sunrise fitting
- 2 x Hot stick end cap
- 2 x Modiewark Spout 150 mm to 300mm
- 1 x PVC Bag With 3 Pockets
- Electrical Stick & Spout Certificate

